



Window Care Kit


For painted and stained wooden windows

Availability	
Quantity per pallet	500
Size / Quantity	Unit
Type of container	Set in carton
Container code	01
Art. no.	
2745	■
The kit includes: 250 ml cleaner, 250 ml balm and 2 special cloths	

Application rate 5-10 ml/m² per coat



Range of use ■ Maintenance of painted and stained wooden windows



Property profile

- Regular use increases the time between maintenance intervals and extends the lifespan of the surfaces
- Revitalises the colour effect/gloss
- Additional protection against the effects of weathering

Characteristic data of the product

Binder	Acrylate
Density (20 °C)	Approx. 1.01 g/cm ³ (2743 Cleaner for Care Kits) Approx. 1.04 g/cm ³ (2744 Wood Balm for Windows)
Odour	Characteristic (2743 Cleaner for Care Kits) Mild (2744 Wood Balm for Windows)


The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates

➤ **Remmers International Guarantee**
Inasmuch as a Remmers International Guarantee (RIG) has been granted, only the conditions / requirements indicated in the written contract between the RIG specialist firm and Remmers shall apply.



Directions



■ Conditions for use

Temperature of the material, air and substrate: from min. +15 °C to max. +25 °C.

Shake well before use.

Soak a cotton cloth with the cleaner and clean the surface; do not rub painted surfaces too intensively.

Leave to dry for approx. 30 minutes.

Using the second special cloth, apply a thin(!) layer of balm quickly, evenly and in one direction (left to right or top to bottom).

Do not buff or rub.

Tips on use



Protect freshly treated surfaces from driving rain, wind, sunlight and condensation.

Do not use on areas directly exposed to sunlight or on heated surfaces.

Do not use at temperatures below 15 °C.

Please only use the special cloths enclosed.

Any material that is not made of wood (e.g. covers, glass, door handles) must not come into contact with the cleaning product. If contact does occur, the material should be rinsed carefully with water.

■ Drying

Approx. 30 minutes

Practice values at +20 °C and 65% relative humidity.

The coating may take significantly longer to dry thoroughly in lower temperatures, at high humidity or if the maximum layer thickness has been exceeded.

■ Thinning

Ready to use

Storage / Shelf life



Store unopened original containers in a cool, dry place protected from frost. Use opened containers promptly within one season after purchase.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

VOC content as per the "Decopaint" Directive (2004/42/EC)

VOC	
Kat.	A/e
2010:	130g/l
max.:	130g/l

Wood Balm for Windows:

EU limit value for the product (Cat. A/e): max. 130 g/l (2010).

This product contains < 130 g/l VOC.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.